

AD-here® CB

Technical Data Sheet	
Description	AD-here® 69-00 is an amidoamine derived adhesion agent which effectively increases the adhesion of cutback asphalt to wet dry aggregates. This product is designed to be very effective on calcareous aggregates.
Typical Properties	Appearance, 77°F: Brown paste Viscosity, 77°F: 8040 cps Viscosity, 100°F: 2440 cps Viscosity, 120°F: 660 cps Density, Pounds/Gallon, 90°F: 7.95 Flash Point (P.M.C.C.) > 300°F
Features	N/A
Applications	The use of 0.5 – 1.5% AD-here® 69-00 by weight of asphalt cement substantially increases the level of aggregate coating and reduces the occurrence of moisture damage.
Advantages	<ul style="list-style-type: none"> • DOT Shipping Non Regulated. • Very effective on calcareous derived aggregates, especially in cutback asphalt applications.
Packaging	N/A
Storage and Handling	Refer to MSDS prior to handling this material. Avoid water contamination during handling and storing. For ease of pumping it is recommended to keep the product at 120° - 140°F. AD-here® 69-00 is available in bulk quantities (1000 - 5500 gal.) and in 55-gallon non-returnable drums (420 pounds net). It is available from our manufacturing location in Mulberry, Florida.
TSCA Compliance	N/A

All suggestions and data are based on information and tests we believe to be reliable. Insofar as applications by prospective users may differ from those recommended, it is suggested the user conduct tests and determine the suitability of the product to his process. No warranty for the application of this product is expressed or implied.