

AD-here® LA-2

Technical Data Sheet	
Description	AD-here® LA-2 is an asphalt anti-stripping agent derived from polyamines. It increases the adhesion of asphalt cement to aggregate and reduces moisture damage.
Typical Properties	Appearance: Dark Brown Liquid Viscosity, 77°F: 300 cps Viscosity, 100°F: 200 cps Pounds/Gallon, 77°F: 8.47 Flash Point (P.M.C.C.)°F > 300°F
Applications	AD-here® LA-2 is added to asphalt in the amount of 0.25 - 1.0% by weight of the asphalt cement, depending on the asphalt and aggregate combination.
Advantages	<ul style="list-style-type: none"> • Effective in reducing moisture damage and in increasing the tensile strength ratio in performance tests such as AASHTO T283, ASTM D4867, LADOTD TR 322M, and similar methods. • Low viscosity.
Packaging	N/A
Storage and Handling	Refer to MSDS prior to handling this material. Avoid water contamination during handling and storing. For ease of pumping it is recommended to keep the product at 100° - 110°F. AD-here® LA-2 is available in bulk quantities (1000 - 5500 gal.) and in 55 gallon non-returnable drums (420# net). It is available from our Convent, Louisiana and Vanceboro, North Carolina manufacturing locations.
TSCA Compliance	N/A

All suggestions and data are based on information and tests we believe to be reliable. Insofar as applications by prospective users may differ from those recommended, it is suggested the user conduct tests and determine the suitability of the product to his process. No warranty for the application of this product is expressed or implied.