

## AD-here® SC-901

Technical Data Sheet		
Description	SC-901 is a 100% active amine based additive that is useful in improving adhesion in hot mix, cold mix, cold patch and anionic hi-float emulsions. The product is unique in that it accomplishes this adhesion without interfering with the emulsification systems.	
Typical Properties	Appearance 25°C: Dark Paste Pounds/Gallon 25°C: 0.91 Flash Point, PMCC: > 150°C Viscosity 38°C: 80-100 cps	
Features	N/A	
Applications	Use Level	Method of Application
Hot mix paving	0.4 - 0.75% (Based on weight of asphalt)	Pretreat asphalt
HFMS-1 HFRS-1	0.1 - 0.25% (Based on weight of emulsion)	Post blend in emulsion or pretreat asphalt
Cold Patch (Cutback or emulsion)	0.5 - 2.0% (Based on Wt. of asphalt)	Pretreat asphalt
Emulsion Cold Mix	0.25 - 0.5% (Based on Wt. of emulsion)	Post blend in emulsion or pretreat asphalt
Packaging	SC-901 is available in bulk quantities and in 210 liter non-returnable drums (170 kg net) or in 1000 kg totes. It is available from our three manufacturing locations: Mulberry, Florida; Convent, Louisiana; and Vanceboro, North Carolina.	
Storage and Handling	Refer to MSDS prior to handling this material. Avoid water contamination during handling and storing.	
TSCA Compliance	N/A	

All suggestions and data are based on information and tests we believe to be reliable. Insofar as applications by prospective users may differ from those recommended, it is suggested the user conduct tests and determine the suitability of the product to his process. No warranty for the application of this product is expressed or implied.