

D-Scent 0119

Technical Data Sheet	
Description	D-Scent 0119 is a proprietary formulation that is used in small quantities to neutralize some of the odors that may be produced by hot asphalt cement. D-Scent 0119 has a high flash point, unlike many of the low flash point products currently being marketed for asphalt odor neutralization.
Typical Properties	Viscosity, 25 °C: 196 cps Specific Gravity, 25°C: 0.97-1.01 Flash Point (Closed cup) > 190° C
Features	N/A
Applications	D-Scent 0119 is typically added at a rate of three or four liters per tank truck of asphalt (0.01-0.02 %). The optimum use level should be determined by trial evaluations. The asphalt cement source and composition as well as the plant's operating temperatures will effect the proper dosage rate. The amount of D-Scent 0119 used per truck of liquid asphalt should be carefully controlled to just neutralize the asphalt odors. It is recommended that each user initially treated incoming asphalt shipments with two liters of D-Scent 0119 then increase the use level in one-half liter increments until the desired result is obtained. Excessive use of D-Scent 0119 will produce a strong aroma that is typically not desired.
Packaging	N/A
Storage and Handling	Refer to MSDS prior to handling this material. D-Scent 0119 is available in 420-lb non-returnable drums and IBC containers from our manufacturing location in Mulberry, Florida.
TSCA Compliance	N/A

All suggestions and data are based on information and tests we believe to be reliable. Insofar as applications by prospective users may differ from those recommended, it is suggested the user conduct tests and determine the suitability of the product to his process. No warranty for the application of this product is expressed or implied.